



N110W

H.265 10-Channel Wi-Fi NVR

N110W supports 10-channel access; it has 4 high-gain antennas and supports dual-band Wi-Fi 6, allowing the Wi-Fi signal of N110W to cover every corner; N110W built-in MIC and Speaker, allowing voice intercom without the need to purchase additional audio equipment; it supports automatic pair IMOU cameras, make N110W connect to camera more easily; N110W supports HDMI and VGA output, and can be adapted to most displays on the market; N110W supports access to APP, allowing users to manage NVR anywhere.



10-Channels Access

Max support for 10-channel, Supports Ethernet and Wi-Fi connections



Automatic Pairing

Effortlessly connects cameras to the NVR for seamless setup



Built-in Mic and Speaker

Achieve two-way talk without extra audio devices



IMOU APP

Access NVR videos anytime, anywhere



Dual-Band Wi-Fi 6(2.4/5GHz)

Each band is recommended for up to 8 channels of 5MP wireless cameras.



HDMI/VGA Output

Enjoy clearer and more detailed visuals



Mass Storage

Support up to 16TB HDD for extended date retention



Four Antennas

Maximizes wireless Four external Wi-Fi antennas coverage ensuring signals reach every corner



4-Channel Playback

Supports 2/4/8/16x playback and intelligent retrieval



H.265 up to 4K UHD


Supports H.265/H.264, maximum output resolution 4K




Third Party Agreement

Supports Onvif, Compatible with more devices

Front View



Back View



Specifications

Video & Audio

Access Channel	10 channels
WiFi Access	2.4G Max 8-channels 5G Max 8-channels
Network Bandwidth	90Mbps
Playback Decoding	4-ch 8MP@15fps 4-ch 5MP@30fps
Video Compression	H.265/H.264
Audio Compression	AAC
Back-up File Format	MP4
Live Display	1,4,8,9,10

Network

Wired Network	1, RJ-45 10/100 Mbps self-adaptive Ethernet interface
Wi-Fi Network	IEEE802.11b/g/n/ax, Wi-Fi 6,2.4GHz & 5GHz
Compatible APP	IMOU APP (IOS & Android)
Third Party Agreement	Onvif

General

Power Supply	DC 12V 2A
Power Consumption	<9W (with HDD Average Power) <19W (with HDD Peak Power)
Working Temperature	-10°C~+45°C
Working Humidity	Less Than 95%RH
Dimension(L×W×H)	241.5mm×260mm×60.2mm (Antenna folded)
Bare Weight	890g(Without HDD)
Certification	CE

What's in the box

WiFi NVR × 1	Power Adapter × 1	Mouse × 1
SATA Power Cable × 1	SATA Data Cable × 1	Ethernet Cable × 1
Screw Pack × 1	Quick Start Guide × 1	Regulatory Information × 1

External Interface

Video Output	1*VGA & 1*HDMI
Audio Input	1*Microphone(Built-in)
Audio Output	1*Speaker(Built-in)
USB Interface	2*USB
Reset Button	YES
Network Interface	1 RJ-45 port (10/100 Mbps)

Special Features

IPC Connection	Automatically connect to IMOU cameras
Smart Detection	Motion / Person / Vehicle
Remote Upgrade	Yes
Sound Channel	Two-Way Audio

Storage

Hard Drive Capacity	1 SATA port, up to 16 TB
Backup Media	USB Flash Drive

Topology Map

